
CHICAGO



Site: calumet river/south chicago, IL



Site: calumet river/south chicago, IL



Site: calumet river/south chicago, IL

- _ former US Steel Factory
- _ built on fill
- _ barge slip remains
- _ concrete pad foundations remain
- _ brick slag containment walls remain
- _ subject to lakefront micro-climate
- _ isolated neighborhood
- _ extreme climate [summer/winter]







CHICAGO


Goals for Sustainability


- _ mixture of uses to create walk-able neighborhood for work and living
- _ energy balance between program elements
- _ on-site energy generation
- _ use site attributes to benefit sustainability
- _ create local industry to replace former role of site
- _ address outdoor comfort





Climate Analysis: temperature analysis





Heating Degree Hours for 18 C


Cooling Degree Hours for 20 Deg C

Annual 75679

Annual 12408



Simulation Model: Office Prototype



The office prototype is a mid-rise building with three stories of open office space. The building is a narrow floor plate oriented from east to west to maximize the opportunities for daylight and ventilation. The core elements are on the west and east facades.

Construction

- A well insulated envelope. U value: 0.250 $\mbox{W/m2-K}$


Openings

- 40% WWR. Double glazed, low e glass

HVAC

- Hot water radiator heating, mixed mode with nat vent, local comfort cooling

Simulation Model: Residential Prototype



The residential prototype is a ten story tower. Each building holds forty units, four units per floor. Ten of these buildings will be necessary to provide the 400 units required.

While ideal solar orientation is east to west, the views to the lake are to the north (lake and Chicago skyline) and the value of that could not be ignored. Therefore the building has been oriented so that each unit will provide a view to the lake.

Construction

- A well insulated envelope. U value: 0.161 $\,\mathrm{W/m2\text{-}K}$

Openings

- 30% WWR. Double glazed, low e glass

HVAC


- Packaged terminal usage with heat recovery

Protoblocks: Strategies for Configuration

- _ maintain view to lake/chicago
- _ create open spaces between buildings for recreation
- _ maintain outdoor comfort in those spaces, solar access
- _ maximize on-site energy generation
- _ reduce travel distance to work
- _ address outdoor comfort



Protoblocks: Shadow Range Studies (1 Hr Time Step)



Summer Solstice Equinox Winter Solstice



Protoblocks: Site Plans

Option 1

Density:

1.0 FAR 19.3 m2/person

Option 2

Density:

0.75 FAR 26.39 m2/person


Option 3


Density:

1.5 FAR 12.69 m2/person





580ft.







Protoblocks: Annual Simulation Results











Adapting to Site and Program: goals in context


- _ mixture of uses to create walk-able neighborhood for work and living
- _ energy balance between program elements
- _ on-site energy generation
- _ use site attributes to benefit sustainability
- _ create local industry to replace former role of site
- _ address outdoor comfort




Data Center: suitability and precedents




Data Center: suitability







Deep Lake Water Cooling: process explained




Energy Balance: program interrelationships - heating




Energy Balance: program interrelationships - transitional



Energy Balance: program interrelationships - cooling



Metro Region: transportation




Metro Region: existing infrastructure




Metro Region: proposed connections



Site Plan: overview



Site Plan: grid diagram



Site Plan: transportation diagram



pedestrian path

vehicle street

bus line

transit station

parking structure

Site Plan: data center locations



data center

heating district

SOM masterplan: comparison



TEAM CHICAGO

SOM

Our energy-based design interfaces with SOM water-oriented scheme

transit corridor onto site, avoid

neighborhood

transit corridor separates

development

heirarchy of roads favoring pedestrians


limited road

typologies scope

replace industry

leisure + retail


Both guard waterfront as public green space, connecting to larger park system




Project Image: bird's eye view



Project Program: floor area breakdown




Design Analysis: walk score






Design Analysis: radiation map



Design Analysis: wind comfort




Site Energy Use: methodology

_ Simulated energy usage of urban design using UMI

_ Sized data center based on hourly heating needs

_ Simulated energy usage of data center using Design Builder





_ Used internal loads of data center simulation to offset heating energy use in buildings

Assumptions: 70% efficiency of heat recovery

10% additional loss in district transmission

Calculated effects of Deep Lake Water Cooling district cooling system


Assumption: Eliminate chiller energy

Double pump energy


Site Energy Use: UMI results




Site Energy Use: simulation results



Site Energy Use: heat energy recovery from data center



Site Energy Use: impact of deep water lake cooling




Site Energy Use: comparisons




Site Energy Use: carbon emission reductions

| Carbon Emissions in RFC West eGRID Subregion | 1,551.52 | ib/mWh | | |
|--|-----------------|---------------|---------------|---------------|
| | Energy Saved/ | Source Energy | Carbon | Total Tons of |
| | Generated [kwh] | Multiplier | Emissions | Carbon Saved |
| | | | [ibs per kWh] | |
| Onsite Photovoltaics | 1,437,801.95 | 3.1 | 1.55152 | 3457.706646 |
| Reusing Data Center Waste Heat | 331,616.23 | 3.1 | 1.55152 | 797.4892804 |
| Using Deep Lake Water Cooling | 261,217.50 | 3.1 | 1.55152 | 628.1904626 |



Conclusions: sustainability and process lessons



sustainability

- _ quantitative and qualitative aspects of sustainability must be balanced
- _ realized the broader range of issues possible to define sustainability
- _ greater breadth of programs would have enabled a more accurate model of neighborhood

process:

- _ working between scales necessary
- _ starting with site specific concerns rather than in abstraction
- _ limitation in accuracy
- _ small scale typology and large scale environmental design studies more effecive over midscale urban block configurations